



FRAME-IN KIT



REFLECTOR TRIM

Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Frame-In Kit		Reflector Trims — See Individual Reflector Trim Specification Sheets							
		Open Downlight						Enclosed Diffusers	Wall Washer
Reflector	Cone	Satin Cone	Baffles	Basic White	Pinhole				
1002F1	NPF 120V	1045	1012	1008	1005	1071	1011	1021	1035
1002FH1	HPF 120V	1046	1013	1008NM	1005WH			1024	1035WH
1002FH2	HPF 277V	1046CD	1013BK	1010	1005NM			1078	1085
			1013WH	1010NM	1005BNM				1095
			1013NM		1076				1096
			1013BKNM		1076WH				1096CD
			1013CD						
			1013CDNM						

Features

- Mounting Frame:** .036" (#20 ga.) galvanized steel. Accommodates all ceilings up to 1" thick; including existing or inaccessible areas. Breakout section and anchor nails permits installation in existing ceilings from below. Push-in/twist-out rotoclips hold reflector flush to ceiling.
- Junction Box:** 4" x 3 1/2" x 2", .063" (#14 ga.) galvanized steel. U.L. listed for maximum of 8 No. 12 ga. 90° C through branch circuit conductors (75° C end of run). Integral cable clamps permit attachment of nonmetallic Romex® or armored cable without need of additional connectors.
- Mounting Bars:** .059" (#16 ga.) galvanized steel. 13" long bars extend to 27", rotatable and lockable, with integral T-bar tabs. Attaches to wood joist or T-bar ceilings without need of accessories.
- Socket Housing:** Impact extruded aluminum precisely attached to reflector by spring clips.
- Socket:** Two-pin Gx23-2 base, molded thermoplastic. Prewired with No. 18 AWM leads to 4" x 3 1/2" x 2" junction box.
- Ballast:** Electromagnetic, encased and potted, class "P". 120 volts or 277 volts; high power factor or normal power factor. Insulation must be kept 3" away from fixture sides and wiring compartment and must not be placed above fixture in a manner which will entrap heat.
- Light Collector:** Die-formed aluminum. Reflects spill light to maximize light output.

Electrical

	120V-NPF	120V-HPF	277V-HPF
Input watts:	17.5	15.5	21.5
Amps:	0.30	0.14	0.085
Minimum starting temperature is 32° F.			

Options & Accessories

- Mounting Bars:** 1964 - 20" set of (2)
T-Bar Anchor Clips: 1956 - set of (4) for use with above bars
Plaster Ceiling Ring: 1960 - 7/8" depth for wet plaster ceilings.
Remodeler Anchor Clip: 1985N

Labels

UL (Suitable for Damp Locations), I.B.E.W.

Romex® is a registered Trademark of General Cable Industries Inc.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2006 Genlyte Group LLC • G0506