



Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
28B70EWH	Matte White	All ProSpec® Track Systems. DO NOT USE with any other mounting accessories, stem mounted Radius® Track, Lytespan Track Systems or ATOM®. Can be wall mounted. NO REMOTE MOUNTING.	Use one of:	70W Ceramic Metal Halide
28B70EBK	Matte Black		8313 8317 83W4	
28B70EAL	Metallic Aluminum		8314 8318 83W6 8316 83W7	

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track.
- Ground Clip:** Ensures proper grounding of module.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

Electrical

Electronic Ballast

Input Voltage: 120V, 60Hz

Power Factor: High

Input Power: 77W

Max. Input Current: 0.64A

Total Harmonic Distortion: <10%

ANSI Code: M139, M143, M98

Do not use on dimming circuit.

Finish

All painted finishes are baked enamel.

Labels

UL, cUL

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • B1108