



Information

Catalog Number	Finish	Diffuser Dia. x Ht.	Mounting Rod Length	Ballast	Lamp
3004PB226U	Polished Brass	19 1/2" X 4 7/64	6 1/2"	Electronic 120/277V	(2) 26W Quad 4-Pin

Features

- 1. Diffuser:** Satin etched opal glass.
- 2. Mounting Stem:** Cast steel. Unit has (3) sets, each set has 3 pcs: (1) 9 1/8" length, (1) 9 1/4" length (removeable), and (1) 4" length.
- 3. Mounting Rod:** cast steel.
- 4. Mounting Knob:** Drilled and tapped steel ball.
- 5. Electrical Chassis:** Die-formed 20 ga. steel, gloss white finish.
- 6. Lamps:** Compact Fluorescent (by others)

Lamping

Compact Fluorescent: (2) 26W Quad tube

	General Electric	Osram/Sylvania	Philips
4-Pin	F26DBXT4/SPX*/4P	CF26DD/E/*	PL-C26W/*/4P

* Manufacturers' color temperature designation.

Electrical

Lampholders: Compact Fluorescent: 4-pin, G24q-3 base

Ballast: Electronic 120/277V

Total Input Watts	53
Max. Line Current (Amps)	.27 / .13
Power Factor	> .98
Ballast Factor	1.03
THD	< 10%
Min. Starting Temps.	-20°C (-4°F)

Labels

UL listed suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®