



Ordering Information

Catalog Number	Finish	Volts	Ballast	Lamping
3020PB	Polished Brass	120V	N/A	(1) A19 100W Max.
3021PB218U	Polished Brass	120/277V	Electronic	(2) 18W Quad 4-Pin

Features

- Diffuser:** Satin etched opal glass.
- Mounting Stems:** Ball stud and die-formed steel.
- Backplate:** Die-formed 20 ga. steel, gloss white finish.
- Mounting Plate:** Die-formed 18 ga. galvanized steel, mounts directly to 4" octagonal outlet box.
- Lamps:** Compact Fluorescent or Incandescent (by others).

Lamping

Incandescent: (1) A-19 100W Max. medium base

Compact Fluorescent: (2) 18W Quad tube

	General Electric	Osram/Sylvania	Philips
4-Pin	F18DBXT4/SPX*/4P	CF18DD/E/*	PL-C18W/*/4P

* Manufacturers' color temperature designation.

Electrical

Lampholders: Incandescent: Medium base, porcelain nickel-plate screw shell
Compact Fluorescent: 4-pin, G24q-2 base

Ballast:	Electronic 120/277V
Total Input Watts	42
Max. Line Current (Amps)	.35 / .15
Power Factor	> .98
Ballast Factor	1.05
THD	< 10%
Min. Starting Temps.	-20°C (-4°F)

Labels

UL listed suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®