



Information

Catalog Number	Finish	Diffuser Dia. x Ht.	Mounting Rod Length	Ballast	Lamp
3040PB	Polished Brass	15 3/4" x 4"	5 1/2"	N/A	(2) A19 60W max.
3040PB218U		15 3/4" x 4"	5 1/2"	Univ. Electronic 120/277V	(2) 18W Quad 4-Pin

Features

- 1. **Diffuser:** Satin etched opal glass.
- 2. **Mounting Rod:** Cast steel.
- 4. **Mounting Knob:** Drilled and tapped steel ball.
- 5. **Electrical Chassis:** Die-formed 20 ga. steel, gloss white finish.
- 6. **Lamps:** Compact Fluorescent or Incandescent (by others).

Labels

UL listed suitable for damp locations.

Lamping

Incandescent: (2) A19 60W Max.

Compact fluorescent: (2) 18W Quad tube

	General Electric	Osram/Sylvania	Philips
4-Pin	F18DBX/SPX*/4P	CF 18DD/E/*	PL-C18W/*/4P

* Manufacturers' color temperature designation.

Electrical

Lampholders: Incandescent: Medium base, porcelain, nickel-plate screw shell
Compact Fluorescent: 4-pin, G24q-2 base

Ballast	Electronic 120/277V
Total Input Watts	42
Max. Line Current (Amps)	.35 / .15
Power Factor	> .98
Ballast Factor	1.05
THD	< 10%
Min. Starting Temps.	-20°C (-4°F)

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®