



Cat. No.	Finish	Lamps	Width	Height	Extension	Ballast(s)	Line Voltage	Line Current, Amps	Input Watts
40602WHN1	Semi-Gloss White	(2) 13W Twin Tube Compact Fluorescent	12 3/8"	11 3/8"	3 1/8"	2-1 Lt. NPF, Magnetic	120V	.60	35
40602WHH1						2-1 Lt. HPF, Magnetic	120V	.28	31
40602WHN2						1-2 Lt. NPF, Magnetic	277V	.56	35
40602WHE1						1-2 Lt. HPF, Electronic	120V	.21	25
40602WHE2						1-2 Lt. HPF, Electronic	277V	.09	25
40602SBN1	Satin Brass	(2) 13W Twin Tube Compact Fluorescent	12 3/8"	11 3/8"	3 1/8"	2-1 Lt. NPF, Magnetic	120V	.60	35
40602SBH1						2-1 Lt. HPF, Magnetic	120V	.28	31
40602SBN2						1-2 Lt. NPF, Magnetic	277V	.56	35
40602SBE1						1-2 Lt. HPF, Electronic	120V	.21	25
40602SBE2						1-2 Lt. HPF, Electronic	277V	.09	25

Features

- Diffuser:** 5/16" thick clear bent glass with perforated pattern ceramic coating inside. Removable by removing (2) knobs, and sliding diffuser out of holder brackets.
- Screen:** (2) Die-formed 20 ga. perforated steel, semi-gloss white finish.
- Ballast(s):** Rated Class "P" thermally protected. See chart above for voltage and power factor options.
- Backplate:** Die-formed 20 ga. steel, matte white finish.
- Holder Bracket:** Extruded aluminum, see above for finishes.

Electrical

Fixtures are rated for connections to 60°C building wire, therefore, they can be used for either old or new construction.

Mounting

Fixture is provided with a mounting plate suitable for direct mounting to most outlet boxes.

Finish

All painted surfaces, baked enamel.

Labels

UL (Suitable for damp locations), I.B.E.W.

Fixture conforms to Americans with Disabilities Act (ADA) Federal Regulations - Protruding Objects.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®

