



Reflector Trim	Frame-In Kit
8096CBW White Cone, White Flange 8096CBA Aluminum Cone, White Flange	S7218HU 7" aperture, 2 lamp 18W Quad Tube CFL (120/277V) 2-pin and 4-pin S7226HU 7" aperture, 2 lamp 26W Quad Tube CFL (120/277V) 2-pin and 4-pin Dimming Options: S7218H <input type="checkbox"/> or S7226H <input type="checkbox"/> CU3 Lightolier PowerSpec 3% Dimming (120/277V) J2LD3 Lutron 5% Dimming (277V) J1MX Mark 10 Dimming (120V) Other dimming product available, please consult factory
	J1LD3 Lutron 5% Dimming (120V) JUM7 Mark 7 Dimming (120/277V) J2MX Mark 10 Dimming (277V)

Features

- Reflector:** 16 ga. Die-formed aluminium, Anobrite® finish.
- Socket Cup:** Die-cast zinc cup effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Mounting Frame:** Die-cast aluminum for dry or plaster ceilings. Accepts other 7" quad tube reflectors.
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Cross Blade Louver:** Die-formed, 16 ga. Aluminum, matte white or painted aluminum finish. Accepts lens (consult factory). 50° cut-off to lamp, medium beam. Keyed for orientation.

Electrical

Note: For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL listed for through branch circuit wiring with max of (8) No. 12 AWG, 90°C supply conductors.

Options and Accessories

Other Louver Finishes

Consult Factory

- | | |
|-----------------------|-----------------------|
| Emergency | Add suffix EM* |
| Chicago Plenum | Add suffix LC |
| Existing/Thk. Ceiling | FA EC7* |

Options and Accessories (continued)

- | | |
|--------------------|------------------------|
| Emergency Ltg. Kit | FA EM3E*(4 pin) |
| | FA EM4E*(4 pin) |
| | FA EM2T*(2 pin) |

Fuse (Slow Blow) Add suffix **F**
 *See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA.
 Sloped Ceiling Adapters; see Specification Sheet SCA.

Labels

UL listed for damp locations, I.B.E.W.

Alzak® is a registered trademark of ALCOA.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2011 Philips Group • C0711

