

Ceiling Cutout: 6 11/16" Dia.

Reflector Trim		Frame-In Kit		
C6P30A CLW	Specular Clear, White Flange	Non-IC	Non-IC AirSeal®	IC-AirSeal®
C6P30A CLP	Specular Clear, Polished Flange	C6120	C6A120	C6AIC
C6P30A CLW30	Specular Clear, White Flange (30° Cut)	75W PAR30	75W PAR30	75W PAR30
C6P30A CLP30	Specular Clear, Polished Flange (30° Cut)	(Short Neck)	(Short Neck)	(Short Neck)
C6P30A <input type="checkbox"/>	Add suffix. See options for other finishes			

Features

- Aperture Cone:** 16 ga. aluminum. Slot cut cone opening minimizes view into fixture. For maximum shielding order the 30° bias cut cone. Keyed to lampholder assembly for true aiming of lamp thru aperture center and to prevent incorrect installation of cone. Available with painted white or polished flange. Interchangeable with other Evolution™ 6" line voltage trims.
- Lampholder Assembly:** Die-cast aluminum "U" shape lamp and accessory holder provided with tension springs for fast snap-in/snap-out side mounting of lamp and various accessories. 35° vertical tilt, 358° horizontal rotation; lockable. Can be relamped without disturbing aiming. Hot aiming can be done with the blade of screwdriver. Accepts up to two 4 3/4" dia. accessories. Can be lamped from above.
- Lamp Ring:** Die-formed aluminum with tension springs to secure lamp. Slide out for relamping. Matte black finish.
- Socket harness:** Medium base porcelain socket with nickel plated screw shell, No. 18 SF-1 leads to keyed plug-in quick connector for power connection to junction box.
- Vertical /Horizontal Locking:** Single screw adjustment and locking system.
- Frame-In-Kit:*** Compatible Frame-In Kits are listed above. See separate Frame-In Kit specification sheets for details.
Non-IC and Non-IC AirSeal® - Insulation must be kept 3" away from fixture sides and wiring compartments and must not be placed above fixture in a manner which will entrap heat.
IC-AirSeal® - Fixture may be in direct contact with insulation.
 *NOTE: For details on Frame-In Kits, see separate specification sheets located in the Accessories / Options section of the Calculite Binder.

Options and Accessories

Reflector Finishes¹

Clear:	CL	Gold:	GD
Black:	BK	White:	WH
Comfort Clear Diffuse:	CCD		
Champagne Bronze:	CCZ		

Options and Accessories (cont.)

¹Specify desired flange: **W** White, **P** Polished
 For 30° Bias cut cone, add suffix "30".

Evolution 6" Trims with Non-IC Frames

C6P30A 1 Primary Color Lens or 1 Secondary Color Lens or 1 Mixing Color Lens and 1 Specialty Filter

C6P30A30 1 Primary Color Lens or 1 Secondary Color Lens or 1 Mixing Color Lens and 1 Specialty Filter

Evolution 6" Trims with AIC Frames

C6P30A 1 Secondary Color Lens or 1 Mixing Color Lens or AF4AS

C6P30A30 1 Secondary Color Lens or 1 Mixing Color Lens or AF4AS

Labels

UL Listed (suitable for damp locations), I.B.E.W.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2011 Genlyte Group LLC • E0711




Accent Lighting Performance Data

(FC) is initial footcandles at center of beam.
 Beam length (**L**) and beam width (**W**) are to where the candlepower is reduced to 50% of the center beam candlepower.


(CBCP) is center beam candlepower.

(C) is distance to the center of the beam.


Lamp data shown is typical, and is based on bare lamp photometrics. Contact lamp manufacturers for availability and performance.



0° Aiming Angle



30° Aiming Angle



30° Aiming Angle

Lamps	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	0° Aiming Angle				30° Aiming Angle				30° Aiming Angle			
				D	FC	L	W	D	C	FC	L	W	D	C	FC

PAR30 (Short Neck) Halogen Line Voltage Lamps

 50W PAR30 NSP	 8°	900	2500	7' 188 1.0' 1.0'	6' 3.5' 166 1.1' 1.0'	2' 3.5' 288 1.1' 0.6'
				10' 92 1.4' 1.4'	9' 5.2' 74 1.7' 1.5'	3' 5.2' 128 1.7' 0.8'
				13' 54 1.8' 1.8'	12' 6.9' 41 2.2' 1.9'	4' 6.9' 72 2.3' 1.1'
				16' 36 2.2' 2.2'	15' 8.7' 27 2.8' 2.4'	5' 8.7' 46 2.6' 1.4'
 50W PAR30 (HIR) SP	 8°	17000	3000	8' 266 1.1' 1.1'	7' 4.0' 225 1.3' 1.1'	3' 5.2' 236 1.7' 0.8'
				12' 118 1.7' 1.7'	10' 5.8' 110 1.9' 1.6'	4' 6.9' 133 2.3' 1.1'
				16' 66 2.2' 2.2'	13' 7.5' 65 2.4' 2.1'	5' 8.7' 85 2.8' 1.4'
				20' 43 2.8' 2.8'	16' 0.2' 43 3.0' 2.6'	6' 10.4' 59 3.4' 1.7'
 50W PAR30 FL	 25°	2000	3000	4' 125 1.8' 1.8'	3' 1.7' 144 1.8' 1.5'	1' 1.7' 250 2.1' 0.9'
				6' 56 2.7' 2.7'	5' 2.9' 52 3.0' 2.6'	2' 3.5' 63 4.2' 1.8'
				8' 31 3.5' 3.5'	7' 4.0' 27 4.2' 3.6'	3' 5.2' 28 6.2' 2.7'
				10' 20 4.4' 4.4'	9' 5.2' 16 5.4' 4.6'	4' 6.9' 16 8.3' 3.5'
 50W PAR30 FL	 35°	1400	3000	3' 156 1.9' 1.9'	3' 1.7' 101 2.6' 2.2'	1' 1.7' 175 3.6' 1.3'
				5' 58 3.2' 3.2'	5' 2.9' 36 4.3' 3.6'	2' 3.5' 44 7.2' 2.5'
				7' 29 4.4' 4.4'	7' 4.0' 19 6.1' 5.1'	3' 5.2' 19 10.8' 3.6'
				9' 17 5.7' 5.7'	9' 5.2' 11 7.8' 6.6'	4' 6.9' 11 14.4' 5.0'
 75W PAR30 NSP	 9°	14000	2500	8' 219 1.3' 1.3'	7' 4.0' 186 1.5' 1.3'	3' 5.2' 194 1.9' 0.9'
				12' 97 1.9' 1.9'	10' 5.8' 91 2.1' 1.8'	4' 6.9' 109 2.6' 1.3'
				16' 55 2.5' 2.5'	13' 7.5' 54 2.7' 2.4'	5' 8.7' 70 3.2' 1.6'
				20' 35 3.1' 3.1'	16' 9.2' 36 3.4' 2.9'	6' 10.4' 49 3.6' 1.9'
 75W PAR30 NFL	 30°	3200	2500	6' 89 3.2' 3.2'	5' 2.9' 83 3.7' 3.1'	2' 3.5' 100 5.5' 2.1'
				8' 50 4.3' 4.3'	7' 4.0' 42 5.1' 4.3'	3' 5.2' 44 8.2' 3.2'
				10' 32 5.4' 5.4'	9' 5.2' 26 6.6' 5.6'	4' 6.9' 25 10.9' 4.3'
				12' 22 6.4' 6.4'	11' 6.4' 17 8.1' 6.8'	5' 8.7' 16 13.7' 5.4'
 75W PAR30 FL	 40°	2000	2500	4' 125 2.9' 2.9'	3' 1.7' 144 3.0' 2.5'	1' 1.7' 250 4.8' 1.5'
				6' 56 4.4' 4.4'	5' 2.9' 52 5.1' 4.2'	2' 3.5' 63 9.7' 2.9'
				8' 31 5.8' 5.8'	7' 4.0' 27 7.1' 5.9'	3' 5.2' 28 14.5' 4.4'
				10' 20 7.3' 7.3'	9' 5.2' 16 9.1' 7.6'	4' 6.9' 16 19.3' 5.8'

Job Information

Type:

Lightolier a Genlyte company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2011 Genlyte Group LLC • E0711