

TRIM NOT SHOWN FOR CLARITY

Ceiling Cutout: 6 9/16" (129 mm) Dia.

Ordering Information

| Reflector Trim | Installation Ring | Lamp Data |
|---|--------------------------|----------------------------|
| C6P30ACCDPEXP Comfort Clear Diffuse, Polished Flange | C6XRM Matte White | 75W PAR30 Halogen E27 240V |

Features

- 1. Reflector Trim:** Low brightness, specular anodized aluminum with integral flange polished to match inside of cone.
- 2. Lamp Holder Assembly:** Unitized optics insure alignment of lamp and aperture cone. Integral C-shaped media holder accepts up to two 4 3/4" dia. accessories.
- 3. Trim Adjustment Mechanism:** Provides 40° vertical tilt, 360°+ horizontal rotation; lockable. EZ-Aim Helical Drive System provides fast and accurate hot aiming with Philips screwdriver.
- 4. Socket harness:** Medium base E27 porcelain socket with nickel plated screw shell. No. 18 (1.0 mm²) SF-1 leads to terminal block for 3 No. 18 (1.0 mm²) supply leads (line, neutral and ground).
- 5. Installation Ring:** Cast aluminum ring is painted and has two 17ga. stainless steel springs that engage in upright position during installation. One touch snap action secures ring in ceiling cutout. ORDER SEPARATELY. See separate specification sheet for details.
- 6. Retention Springs:** Rust resistant springs secure trim for quick, tool-less installation (quantity of 4).

Accessories

- 1 Primary Color Lens or 1 Secondary Color Lens or 1 Mixing Color Lens and 1 Specialty Filter

Certifications and Ratings



| Job Information | Type: |
|------------------|-------|
| Job Name: | |
| Cat. No.: | |
| Lamp(s): | |
| Notes: | |

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2011 Philips Group • B0711


Accent Lighting Performance Data

(FC) is initial footcandles at center of beam.
 Beam length (**L**) and beam width (**W**) are to where the candlepower is reduced to 50% of the center beam candlepower.


CBCP is center beam candlepower.

(C) is distance to the center of the beam.


Lamp data shown is typical, and is based on bare lamp photometrics. Contact lamp manufacturers for availability and performance.



0° Aiming Angle



30° Aiming Angle



30° Aiming Angle

Lamps Beam Spread (To 50% CBCP) CBCP Rated Life (Hrs.)

D FC L W

D C FC L W

D C FC L W

PAR30 (Short Neck) Halogen Line Voltage Lamps

| Lamps | Beam Spread (To 50% CBCP) | CBCP | Rated Life (Hrs.) | D | FC | L | W | D | C | FC | L | W | D | C | FC | L | W |
|--------------------|---------------------------|-------|-------------------|-----|-----|------|------|-----|------|-----|------|------|----|-------|-----|-------|------|
| 50W PAR30 NSP | 8° | 900 | 2500 | 7' | 188 | 1.0' | 1.0' | 6' | 3.5' | 166 | 1.1' | 1.0' | 2' | 3.5' | 288 | 1.1' | 0.6' |
| | | | | 10' | 92 | 1.4' | 1.4' | 9' | 5.2' | 74 | 1.7' | 1.5' | 3' | 5.2' | 128 | 1.7' | 0.8' |
| | | | | 13' | 54 | 1.8' | 1.8' | 12' | 6.9' | 41 | 2.2' | 1.9' | 4' | 6.9' | 72 | 2.3' | 1.1' |
| | | | | 16' | 36 | 2.2' | 2.2' | 15' | 8.7' | 27 | 2.8' | 2.4' | 5' | 8.7' | 46 | 2.6' | 1.4' |
| 50W PAR30 (HIR) SP | 8° | 17000 | 3000 | 8' | 266 | 1.1' | 1.1' | 7' | 4.0' | 225 | 1.3' | 1.1' | 3' | 5.2' | 236 | 1.7' | 0.8' |
| | | | | 12' | 118 | 1.7' | 1.7' | 10' | 5.8' | 110 | 1.9' | 1.6' | 4' | 6.9' | 133 | 2.3' | 1.1' |
| | | | | 16' | 66 | 2.2' | 2.2' | 13' | 7.5' | 65 | 2.4' | 2.1' | 5' | 8.7' | 85 | 2.8' | 1.4' |
| | | | | 20' | 43 | 2.8' | 2.8' | 16' | 9.2' | 43 | 3.0' | 2.6' | 6' | 10.4' | 59 | 3.4' | 1.7' |
| 50W PAR30 FL | 25° | 2000 | 3000 | 4' | 125 | 1.8' | 1.8' | 3' | 1.7' | 144 | 1.8' | 1.5' | 1' | 1.7' | 250 | 2.1' | 0.9' |
| | | | | 6' | 56 | 2.7' | 2.7' | 5' | 2.9' | 52 | 3.0' | 2.6' | 2' | 3.5' | 63 | 4.2' | 1.8' |
| | | | | 8' | 31 | 3.5' | 3.5' | 7' | 4.0' | 27 | 4.2' | 3.6' | 3' | 5.2' | 28 | 6.2' | 2.7' |
| | | | | 10' | 20 | 4.4' | 4.4' | 9' | 5.2' | 16 | 5.4' | 4.6' | 4' | 6.9' | 16 | 8.3' | 3.5' |
| 50W PAR30 FL | 35° | 1400 | 3000 | 3' | 156 | 1.9' | 1.9' | 3' | 1.7' | 101 | 2.6' | 2.2' | 1' | 1.7' | 175 | 3.6' | 1.3' |
| | | | | 5' | 58 | 3.2' | 3.2' | 5' | 2.9' | 36 | 4.3' | 3.6' | 2' | 3.5' | 44 | 7.2' | 2.5' |
| | | | | 7' | 29 | 4.4' | 4.4' | 7' | 4.0' | 19 | 6.1' | 5.1' | 3' | 5.2' | 19 | 10.8' | 3.6' |
| | | | | 9' | 17 | 5.7' | 5.7' | 9' | 5.2' | 11 | 7.8' | 6.6' | 4' | 6.9' | 11 | 14.4' | 5.0' |
| 75W PAR30 NSP | 9° | 14000 | 2500 | 8' | 219 | 1.3' | 1.3' | 7' | 4.0' | 186 | 1.5' | 1.3' | 3' | 5.2' | 194 | 1.9' | 0.9' |
| | | | | 12' | 97 | 1.9' | 1.9' | 10' | 5.8' | 91 | 2.1' | 1.8' | 4' | 6.9' | 109 | 2.6' | 1.3' |
| | | | | 16' | 55 | 2.5' | 2.5' | 13' | 7.5' | 54 | 2.7' | 2.4' | 5' | 8.7' | 70 | 3.2' | 1.6' |
| | | | | 20' | 35 | 3.1' | 3.1' | 16' | 9.2' | 36 | 3.4' | 2.9' | 6' | 10.4' | 49 | 3.6' | 1.9' |
| 75W PAR30 NFL | 30° | 3200 | 2500 | 6' | 89 | 3.2' | 3.2' | 5' | 2.9' | 83 | 3.7' | 3.1' | 2' | 3.5' | 100 | 5.5' | 2.1' |
| | | | | 8' | 50 | 4.3' | 4.3' | 7' | 4.0' | 42 | 5.1' | 4.3' | 3' | 5.2' | 44 | 8.2' | 3.2' |
| | | | | 10' | 32 | 5.4' | 5.4' | 9' | 5.2' | 26 | 6.6' | 5.6' | 4' | 6.9' | 25 | 10.9' | 4.3' |
| | | | | 12' | 22 | 6.4' | 6.4' | 11' | 6.4' | 17 | 8.1' | 6.8' | 5' | 8.7' | 16 | 13.7' | 5.4' |
| 75W PAR30 FL | 40° | 2000 | 2500 | 4' | 125 | 2.9' | 2.9' | 3' | 1.7' | 144 | 3.0' | 2.5' | 1' | 1.7' | 250 | 4.8' | 1.5' |
| | | | | 6' | 56 | 4.4' | 4.4' | 5' | 2.9' | 52 | 5.1' | 4.2' | 2' | 3.5' | 63 | 9.7' | 2.9' |
| | | | | 8' | 31 | 5.8' | 5.8' | 7' | 4.0' | 27 | 7.1' | 5.9' | 3' | 5.2' | 28 | 14.5' | 4.4' |
| | | | | 10' | 20 | 7.3' | 7.3' | 9' | 5.2' | 16 | 9.1' | 7.6' | 4' | 6.9' | 16 | 19.3' | 5.8' |

Job Information **Type:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2011 Philips Group • B0711