



Ordering Information

Catalog No.	Rating	Finish	Mounting	Compatible Connector Kits
CLD120WH	1.0a, 120W	White	Snaps in directly to any compatible PowerTrip Connector Kit	9099WH, BK
CLD120BK	1.0a, 120W	Black		9033WH, BK
CLD300WH	2.5a, 300W	White		6099WH, BK
CLD300BK	2.5a, 300W	Black		6033WH, BK
CLD600WH	5.0a, 600W	White		6199WH, BK
CLD600BK	5.0a, 600W	Black		6133WH, BK
CLD900WH	7.5a, 900W	White		
CLD900BK	7.5a, 900W	Black		

Features

1. Wire Terminals: #8 screws for 12 or 14 ga. solid copper wires.
2. Reset Rocker: Easy switch like breaker re-set actuator with ON/OFF markings. Red color indicates OFF position. Can be used as standard ON/OFF switch
3. Panel Mount: Breaker snaps into PowerTrip track connector without the use of tools.

Note: to assure full compliance with local energy codes and regulations check with your local code official.

Electrical

Capacity is 120 volts, 60Hz. All Lytespan Track luminaires are polarized and continuously grounded throughout. Electrical conductors are concealed in an insulating liner. Intended for wiring to branch circuit building wire with ground. All wiring must be in accordance with National and Local Codes.

Short Circuit Current Rating (AIC): 1kA

Use 90° C minimum supply wire.

Labels

U.L. listed.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	