



3 Piece Ordering System: Complete Fixture consists of Decorative Element, Calculite Light Engine, and Calculite Frame-In Kit. Each sold separately.

Aperture	Decorative Element Catalog No.	Frame-In Kit and Trim	Wattage	Dimensions		
				A	B	C
4"	D4A13	C4L05 Series	10W	5 1/8"	8 1/2"	2 1/4"
		C4L10 Series	20W			

Features

1. **Decorative Element:** Inner: angled hand blown triplex glass carefully proportioned to each aperture size. Glass is gently and evenly illuminated for clean brightness recognition. Outer: angled hand blown clear glass.
2. **Die Cast Finish Ring:** Aluminum Die Cast finish ring with crisp 90 degree edges conceals all fasteners for a clean finished appearance.
3. **Die Cast Construction Ring:** Internal die cast construction ring is mechanically attached to frame in kit and is concealed by finish ring.
4. **Mounting Frame Fasteners:** Four #8-32 screws and 4 knurled die-cast thumb screws secure construction ring to frame in kit.
5. **Reflector:** FLANGELESS TRIM REQUIRED. Specified separately. Use Specular Clear (CL) finish for best performance and aesthetics.
6. **Frame-In Kit:** Specified separately. See Trim Kit Specification Sheet for additional details.

Mechanical

Decorative element is mechanically secured to the die cast construction ring and the integral reflector from the factory.

Labels

cULus (Damp Location)

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	