

PB2P3810BL = (Flanged) Black/White
PB2P3810WL = (Flanged) White

PB2P3810BTL = (Trimless) Black
PB2P3810WTL = (Trimless) White

Ceiling Cutout: 15 1/16" L X 8 3/16" W

Ordering Information: PAR 38 Series B

Cat. No.	Lamp	Ceiling Trim	Aperture Finish
PB2P3810BL	(2) 100W PAR38	Overlap	Black with White Flange
PB2P3810WL	(2) 100W PAR38	Overlap	White with White Flange
PB2P3810BTL	(2) 100W PAR38	Trimless	Black
PB2P3810WTL	(2) 100W PAR38	Trimless	White

Features

- Aperture Frame:** Provides clean support for lamp holders and overlapping flange or trimless installation. Extruded aluminum. Rigidly welded together on all corners.
- Media Cartridge:** Allows convenient loading and removal of one accessory. Easily installed and removed for lamping with a simple twisting motion. Constructed of die formed aluminum.
- Adjustable Ring:** Allows 360° horizontal and 30°, max. 45° (on length); 40° (on width) vertical adjustment.
- Tortiontite Spring:** For easy installation of aperture frame.
- Housing:** Die-formed 22 ga. steel. Finish: Black
- Mounting Brackets:** Adjustable vertically from outside of housing.
- Thermal Protector:** Meets NEC, UL, and CSA requirements.
- Lampholder:** Porcelain medium based; nickel plated screw shell. Prewired with #18 SF-1 leads to junction box.
- Junction Box:** 14 ga. steel, 4" x 3 1/2" x 2" box. Allows inspection from below.
- Lamp and Accessory Support:** .032" steel, flared for easy entry of Media Cartridge.
- Lens Retaining Ring:** .093" spring steel rod. Holds accessories in place.

Electrical

UL/cUL listed for through branch circuit wiring with maximum of (8) no. 12 AWG, 90° C.

Finish

All painted finishes are powder coated baked enamel.

Options & Accessories

Accessories: 4 3/4" dia. series, filters, lenses, screens, and louvers (1) max.

Labels

UL/cUL (Suitable for Damp Location), I.B.E.W.

Job Information


Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:



Lighting Performance Data

		Narrow																			
		45W PAR38 NSP (T-H)	45W PAR38 SP (T-H)	75W PAR38 SP	90W PAR38 NSP (T-H)	90W PAR38 SP (T-H)															
DISTANCE																					
FOOTCANDLES (On Beam Center At 6')		236	131	144	528	333															
BEAM SPREAD (To 50% Max. CP)		6°	14°	12°	7°	12°															
MAX. CANDLEPOWER (Candelas)		8,500	4,700	5,200	19,000	12,000															
RATED LIFE (Hours)		2,000		2,000		2,000															
0° AIMING ANGLE Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W				
	7'	173	0.7'	0.7'	8'	131	1.5'	1.5'	6'	144	1.3'	1.3'	10'	190	1.2'	1.2'	8'	188	1.7'	1.7'	
	10'	85	1.0'	1.0'	8'	73	2.0'	2.0'	8'	81	1.7'	1.7'	15'	84	1.8'	1.8'	12'	83	2.5'	2.5'	
	13'	50	1.4'	1.4'	10'	47	2.5'	2.5'	10'	52	2.1'	2.1'	20'	47	2.4'	2.4'	16'	47	3.4'	3.4'	
30° AIMING ANGLE Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W
	6'	153	0.8'	0.7'	5'	122	1.6'	1.4'	5'	135	1.4'	1.2'	8'	193	1.3'	1.1'	7'	159	2.0'	1.7'	
	9'	68	1.3'	1.1'	7'	62	2.3'	2.0'	7'	69	2.0'	1.7'	12'	86	2.0'	1.7'	10'	78	2.8'	2.4'	
30° AIMING ANGLE Illumination on Vertical Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W
	2'	266	0.8'	0.4'	2'	147	2.1'	1.0'	2'	163	1.7'	0.8'	4'	148	2.0'	1.0'	3'	167	2.6'	1.3'	
	3'	118	1.3'	0.6'	3'	65	3.1'	1.5'	3'	72	2.6'	1.3'	6'	66	3.0'	1.5'	4'	94	3.5'	1.7'	

		Medium											
		45W PAR38 FL (T-H)	75W PAR38 FL	90W PAR38 FL (T-H)									
DISTANCE													
FOOTCANDLES (On Beam Center At 6')		47	52	111									
BEAM SPREAD (To 50% Max. CP)		28°	30°	30°									
MAX. CANDLEPOWER (Candelas)		1,700	1,860	4,000									
RATED LIFE (Hours)		2,000		2,000									
0° AIMING ANGLE Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
	3'	189	1.5'	1.5'	4'	116	2.1'	2.1'	6'	111	3.2'	3.2'	8'
	5'	68	2.5'	2.5'	6'	52	3.2'	3.2'	8'	63	4.3'	4.3'	10'
	7'	35	3.5'	3.5'	8'	29	4.3'	4.3'	10'	40	5.4'	5.4'	12'
30° AIMING ANGLE Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
	3'	123	2.0'	1.7'	5'	134	2.2'	1.9'	5'	104	3.7'	3.1'	7'
	5'	44	3.4'	2.9'	7'	48	3.7'	3.1'	7'	53	5.1'	4.3'	9'
30° AIMING ANGLE Illumination on Vertical Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
	1'	213	2.5'	1.0'	1'	233	2.7'	1.1'	2'	125	5.5'	2.1'	3'
	2'	53	4.9'	2.0'	2'	58	5.5'	2.1'	3'	56	8.2'	3.2'	4'

Data are based on bare lamp photometrics. FC is initial footcandles at center of beam. L and W are to the point that the candlepower drops 50% of maximum.

Beam Center Location

Distance D (ft.)	1	2	3	4	5	6	7	8	9	10
Distance C (ft.)	1.7	3.5	5.2	6.9	8.7	10.4	12.1	13.8	15.6	17.3

This chart locates the distance (C) to the center of the light beam for various distances (D) when the lamp is aimed 30° from vertical, the preferred aiming angle for lighting pictures on a wall.

Job Information **Type:**

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2011 Genlyte Thomas Group LLC (Lightolier Division) • B0711

LIGHTOLIER®