



Catalog Number	Rating	Finish/Description	Mounting	Compatible Connector Kits
PSP9ABK	180W/2493W, 9.0A	Black	Snaps in directly to compatible PowerTrip ProSpec Connector Kit	26099WH/BK 37099WH/BK
PSP9AWH		White		
PSP10ABK	1200W/2770W, 10.0A	Black		
PSP10AWH		White		
PSP1ABK	120W/277W, 1.0A	Black		
PSP1AWH		White		
PSP11ABK	1320W/3047W, 11.0A	Black		
PSP11AWH		White		
PSP12ABK	1440W/3324W, 12.0A	Black		
PSP12AWH		White		
PSP2ABK	240W/554W, 2.0A	Black		
PSP2AWH		White		
PSP25ABK	300W/692W, 2.5A	Black		
PSP25AWH		White		
PSP3ABK	360W/831W, 3.0A	Black		
PSP3AWH		White		
PSP4ABK	480W/1108W, 4.0A	Black		
PSP4AWH		White		
PSP5ABK	600W/1385W, 5.0A	Black		
PSP5AWH		White		
PSP6ABK	720W/1662W, 6.0A	Black		
PSP6AWH		White		
PSP7ABK	840W/1939W, 7.0A	Black		
PSP7AWH		White		
PSP75ABK	900W/2077W, 7.5A	Black		
PSP75AWH		White		
PSP8ABK	960W/2216W, 8.0A	Black		
PSP8AWH		White		

Features

- Wires:** (2) 12 ga. insulated wires, 6" long, tin coated with 1/2" strip lengths.
- Reset Rocker:** Easy switch like breaker re-set actuator with ON/OFF markings. Red color indicates OFF position. Can be used as standard ON/OFF switch
- Panel Mount:** Breaker snaps into PowerTrip track connector without the use of tools.
- Crimp-on Connectors:** Female disconnect, funnel entry, with (1) strip of fiberglass tape.

Electrical

Capacity is 277 volts, 60Hz. All Prospec Track luminaires are polarized and continuously grounded throughout. Electrical conductors are concealed in an insulating liner. Intended for wiring to branch circuit building wire with ground. All wiring must be in accordance with National and Local Codes. Short Circuit Current Rating (AIC): 1kA Use 90° C minimum supply wire.

Labels

UL listed

Note: To assure full compliance with local energy codes and regulations check with local code official

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	