



## Features

1. **Housing:** Extruded Aluminum
2. **End Caps:** Cast Aluminum
3. **Diffuser:** Injection Molded, UV Resistant Acrylic
4. **Wall Mount:** Cast Aluminum
5. **Junction Box Mounting Plate:** 18ga. C.R.S. zinc plated. For mounting to standard 4" octagonal junction box.
6. **Lampholder:** Fluorescent, 2G11 Base

## Mechanical

Diffuser Assembly Securely Fastens to Housing using (2) Countersunk Screws and (2) Pressure Fit Fasteners

## Finish

Gloss White

## Lamping

Lamp	Philips	General Electric	Osram/Sylvania
(1) 18W Twin Tube	PL-L 18W/*/4P	F18BX/SPX* 10PK	FT18DL/*/*RS**

\*Manufacturers Color Temperature Designation

\*\*Provides Most Even Illumination

## Ballast-Electronic 120-277V

Voltage	120V	277V
Total Input Watts	23W	23W
Max. Line Current (Amps)	0.19A	0.07A
Ballast Factor	1.00	1.00
THD	<10%	<10%
Min. Starting Temp.	0°F	0°F

## Labels

cULus Listed

Suitable for Damp Locations

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**